



## Baudouin EcoMax B2250-S | B2550-S | B2750-S

Baudouin Powered Diesel Engine Coupled to Stamford AVK Alternator, Fully Designed in The United Kingdom Controlled by a DSE Auto Start Digital Controller.

| Model   | Baudouin     | Stamford | Deepsea   | Prime      | Standby    | Phase |
|---------|--------------|----------|-----------|------------|------------|-------|
| B2250-S | 16M33G2250/5 | S7L1D-G  | 7320 MKII | 2000.0 kVA | 2250.0 kVA | 3     |
| B2550-S | 20M33G2500/5 | S7L1D-J  | 7320 MKII | 2300.0 kVA | 2550.0 kVA | 3     |
| B2750-S | 12M55G2750/5 | S7L1D-J  | 7320 MKII | 2500.0 kVA | 2750.0 kVA | 3     |

### EcoMax Series Canopies default features

- Compatible with 2000/14/EC directives, certified noise emission level
- 2 or 4 points transport possibility according to canopy size.
- Hidden residential low noise exhaust built in the canopy.
- Emergency stop button located on the canopy
- Acoustic vents for Improved air suction channel to ensure homogenous cooling in the canopy.
- Radiator air outlet and exhaust with designed towards above
- Galvanised & Powder Coated against corrosion and rust.
- Improved performance in terms of sound insulation.



### EcoMax Base Frame & Fuel Tank

Base is manufactured from galvanised steel that has features and durability. Thanks to its rigid structural design and anti-vibration mounts, it reduces vibration level to minimum. Base frame contain lifting points to make transportation and positioning easy. With integrated modular fuel tank

### DeepSea Electronics DSE7320 Controller

The DSE7310 is an Auto Start Control Module and the DSE7320 is an Auto Mains (Utility) Failure Control Module suitable for a wide variety of single, diesel or gas, gen-set applications.

Monitoring an extensive number of engine parameters, the modules will display warnings, shutdown and engine status information on the back-lit LCD screen, illuminated LEDs, remote PC and via SMS text alerts (with external modem).



| Dimensions              | Length [mm] | Width [mm] | Hight [mm] | Weight [kg] | Fuel Capacity [LT] | Sound Level [dBA] |
|-------------------------|-------------|------------|------------|-------------|--------------------|-------------------|
| <b>B2250 Open</b>       | 5973        | 2756       | 3055       | 9262        | 3000               | N/A               |
| <b>B2250-S Canopied</b> | 8360        | 2560       | 3242       | 18417       | 3000               | TBC               |
| <b>B2550 Open</b>       | 6524        | 2300       | 2834       | TBC         | 3000               | N/A               |
| <b>B2550-S Canopied</b> | 8360        | 2560       | 3242       | TBC         | 3000               | TBC               |
| <b>B2750 Open</b>       | 6002        | 2300       | 2972       | TBC         | 3000               | N/A               |
| <b>B2750-S Canopied</b> | 8360        | 2560       | 3242       | TBC         | 3000               | TBC               |

### Engine

Blackwell Generators provides industrial diesel engines that meet ISO 8528 and ISO 3046 specifications. These engines are designed for heavy-duty applications, offering low fuel consumption and precise speed adjustment and regulation. They are equipped with mechanical or electronic governors mounted on the fuel pump and are available with oil, air, or water cooling systems to suit specific operational requirements. The engines are built with robust oil, fuel, and air filtration systems tailored for demanding operational conditions, ensuring long life and high performance. They are 4-stroke, direct-injection engines with all necessary limit and level sensors for safe operation. Engines designed exclusively for standby use are excluded from the production portfolio.

### Alternator

Blackwell Generators incorporates original European-brand alternators in its generator sets, fully complying with international standards such as IEC 60034-1, ISO 8528-3, EN 55011, BS 4999-5000, and VDE 0530. These alternators deliver high efficiency and superior performance under all conditions and are certified to meet global quality standards.

### Cooling Systems

Radiators in Blackwell generators are selected from original options or approved vendor lists of engine manufacturers. These radiators are designed to optimise usability, spare part availability, high performance, and maximum efficiency. Remote-type radiators capable of handling temperatures up to 55°C can also be provided.

### Frame

Blackwell Generators manufactures frames for all generator sets based on international standards. The frames are designed and constructed using plate panels or profiles to ensure high resistance to vibration and stresses, providing long-lasting durability.

### Documentation

Blackwell Generators provides comprehensive documentation with every generator set, including:

- Maintenance and operation manual
- Engine and alternator manuals
- Controller usage and maintenance booklet
- Warranty certificate
- Electrical diagrams

### Warranty

The warranty period for Blackwell Generators begins on the invoice date and covers up to **1 year or 1,000 operational hours**, whichever comes first.

|                                                                                                                                                                                                                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>Authorised Dealer:</p> <div style="text-align: right;">   </div> |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Disclaimer: Blackwell Generators is proudly owned and distributed by FW Power Generators Limited, a UK-based company registered in England and Wales (Company Registration Number: 15932066).

In accordance with our commitment to continuous product improvement, we reserve the right to modify specifications without prior notice.

UK & International Sales: +44 (0)1829 863 497 | [www.blackwellgenerators.com](http://www.blackwellgenerators.com) | [info@blackwellgenerators.com](mailto:info@blackwellgenerators.com)