

MODEL P13-BWP


13.9 kVA
ESP

11.1 kW
ESP

12.8 kVA
PRP

10.2 kW
PRP

50 HZ | PRIME & STANDBY POWER



DIESEL ENGINE	
ENGINE BRAND	Perkins
ENGINE MODEL	403A-15G1
ASPIRATION	Naturally Aspirated
GOVERNOR	Mechanical

ALTERNATOR	
BRAND	Stamford
MODEL	S0L2-G1
EXCITATION	Self Excited
INSULATION CLASS	H
VOLTAGE REGULATION	1%
SPACE HEATER	Optional

GENERATOR SET - KEY PARAMETERS	
GENSET MODEL	P13-BWP
POWER PRP	12.8 kVA / 10.2 kW
POWER ESP	13.9 kVA / 11.1 kW
FREQUENCY / SPEED	50 Hz / 1500 RPM
OUTPUT VOLTAGE	400 / 230 V
WIRING METHOD	3-phase, 4-wire
POWER FACTOR	0.8 pf lagging
ENCLOSURE / NOISE	Canopied; 76 dB(A) @ 7 m

AUXILIARY SYSTEMS	
CONTROL MODULE	Deep Sea DSE 7320 MKII
COOLING RADIATOR	Tropical, 50 C ambient
FULL-LOAD CURRENT	20.1 A at ESP
CIRCUIT BREAKER	Optional; sized to generator rating
COOLANT HEATER	Optional
STARTING BATTERY	Wet battery, maintenance-free
FUEL TANK	80 litres
BASE FRAME	Base tank + AVM + battery holder



Acoustic Vents



Premium DSE Controller



Easy Maintenance

STANDARD SUPPLY	
INSTALLATION ACCESSORIES	AVMs, exhaust connection, silencer, standard connection parts and tool kit.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

MODEL P13-BWP

13.9 kVA
ESP

11.1 kW
ESP

12.8 kVA
PRP

10.2 kW
PRP

50 HZ | PRIME & STANDBY POWER

ENGINE TECHNICAL PARAMETERS - PERKINS 403A-15G1 - DIESEL

STRUCTURAL FORM	4 Stroke	COMBUSTION SYSTEM	Direct Injection
NUMBER OF CYLINDERS	3 (In Line)	OIL CAPACITY	6.0L
DISPLACEMENT	1.496L	COOLANT CAPACITY	6.0L
BORE / STROKE	84mm / 90mm	MAX EXHAUST TEMP.	580 °C
COMPRESSION RATIO	22.5:1	EU EMISSIONS	None
ASPIRATION	Naturally Aspirated		
GOVERNOR	Mechanical		
COOLING METHOD	Liquid Cooled		
SPEED	1500 RPM		

FUEL CONSUMPTION

50% Load 2.04 litres/hour	75% Load 2.79 litres/hour	100% Load 3.67 litres/hour	110% Load 4.08 litres/hour
------------------------------	------------------------------	-------------------------------	-------------------------------

ALTERNATOR TECHNICAL PARAMETERS - STAMFORD S0L2-G1

RATED POWER AT 400 V	ESP 22.0 kVA / PRP 20.0 kVA
NUMBER OF POLES / LEADS	4 / 12
WINDING NUMBER	311
BEARING TYPE	1 bearing
PROTECTION CLASS	IP23
INSULATION CLASS	H
EXCITATION METHOD	Self Excited
VOLTAGE REGULATION	AS540 AVR / 1%
HARMONIC CONTENT	<5.00%
SHORT-CIRCUIT CAPACITY	>100%
SPACE HEATER	Optional

CONTROL SYSTEM - DSE 7320 MKII

BRAND	Deep Sea Electronics
MODEL	DSE 7320 MKII
CONFIGURABLE INPUTS / OUTPUTS	6 digital + 3 analogue senders / 6 outputs
KEY FEATURES	Auto-start, AMF control, LED indicators and event logging

MODEL P13-BWP

13.9 kVA
ESP

11.1 kW
ESP

12.8 kVA
PRP

10.2 kW
PRP

50 HZ | PRIME & STANDBY POWER



DIMENSIONS & WEIGHT			
LENGTH (mm) 2240	WIDTH (mm) 1038	HEIGHT (mm) 1378	WEIGHT (kg) 838.75

Configuration: UK/EU Canopied / frame 1900E / tank 80 L

RATING CONDITIONS	
RATING BASIS	NTP conditions; confirm project derating requirements
FREQUENCY / SPEED	50 Hz / 1500 RPM
VOLTAGE / CONNECTION	400/230 V / series star
POWER FACTOR	0.8 lagging
COOLING PACKAGE	Tropical radiator rated for 50 C ambient
STANDARDS	ISO 8528; IEC 60034

DISCLAIMER

Ratings and component data are transcribed from the corresponding Welland Power configuration for 400 V, three-phase, 50 Hz operation and checked against the listed Perkins engine and Stamford alternator models. Dimensions, weight, tank and noise data apply only to the configuration stated above. Images are illustrative and are intentionally common across this range. Final build specification, GA drawing, breaker selection and site derating must be confirmed at order. Manufacturer specifications may change without notice.

Dealer contact details: