

MODEL P20-BWP

21.2 kVA
ESP

17.0 kW
ESP

19.6 kVA
PRP

15.7 kW
PRP

50 HZ | PRIME & STANDBY POWER



DIESEL ENGINE

ENGINE BRAND	Perkins
ENGINE MODEL	404A-22G
ASPIRATION	Naturally Aspirated
GOVERNOR	Mechanical

ALTERNATOR

BRAND	Stamford
MODEL	S0L2-G1
EXCITATION	Self Excited
INSULATION CLASS	H
VOLTAGE REGULATION	1%
SPACE HEATER	Optional

GENERATOR SET - KEY PARAMETERS

GENSET MODEL	P20-BWP
POWER PRP	19.6 kVA / 15.7 kW
POWER ESP	21.2 kVA / 17.0 kW
FREQUENCY / SPEED	50 Hz / 1500 RPM
OUTPUT VOLTAGE	400 / 230 V
WIRING METHOD	3-phase, 4-wire
POWER FACTOR	0.8 pf lagging
ENCLOSURE / NOISE	Canopied; 76 dB(A) @ 7 m

AUXILIARY SYSTEMS

CONTROL MODULE	Deep Sea DSE 7320 MKII
COOLING RADIATOR	Tropical, 50 C ambient
FULL-LOAD CURRENT	30.6 A at ESP
CIRCUIT BREAKER	Optional; sized to generator rating
COOLANT HEATER	Optional
STARTING BATTERY	Wet battery, maintenance-free
FUEL TANK	80 litres
BASE FRAME	Base tank + AVM + battery holder



Acoustic Vents



Premium DSE Controller



Easy Maintenance

STANDARD SUPPLY

INSTALLATION ACCESSORIES	AVMs, exhaust connection, silencer, standard connection parts and tool kit.
--------------------------	---

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

MODEL P20-BWP

21.2 kVA
ESP

17.0 kW
ESP

19.6 kVA
PRP

15.7 kW
PRP

50 HZ | PRIME & STANDBY POWER

ENGINE TECHNICAL PARAMETERS - PERKINS 404A-22G - DIESEL

STRUCTURAL FORM	4 Stroke	COMBUSTION SYSTEM	Direct Injection
NUMBER OF CYLINDERS	4 (In Line)	OIL CAPACITY	10.6L
DISPLACEMENT	2.216L	COOLANT CAPACITY	7.0L
BORE / STROKE	84mm / 100mm	MAX EXHAUST TEMP.	505 °C
COMPRESSION RATIO	23.3:1	EU EMISSIONS	None
ASPIRATION	Naturally Aspirated		
GOVERNOR	Mechanical		
COOLING METHOD	Liquid Cooled		
SPEED	1500 RPM		

FUEL CONSUMPTION

50% Load 2.90 litres/hour	75% Load 4.00 litres/hour	100% Load 5.30 litres/hour	110% Load 6.10 litres/hour
------------------------------	------------------------------	-------------------------------	-------------------------------

ALTERNATOR TECHNICAL PARAMETERS - STAMFORD S0L2-G1

RATED POWER AT 400 V	ESP 22.0 kVA / PRP 20.0 kVA
NUMBER OF POLES / LEADS	4 / 12
WINDING NUMBER	311
BEARING TYPE	1 bearing
PROTECTION CLASS	IP23
INSULATION CLASS	H
EXCITATION METHOD	Self Excited
VOLTAGE REGULATION	AS540 AVR / 1%
HARMONIC CONTENT	<5.00%
SHORT-CIRCUIT CAPACITY	>100%
SPACE HEATER	Optional

CONTROL SYSTEM - DSE 7320 MKII

BRAND	Deep Sea Electronics
MODEL	DSE 7320 MKII
CONFIGURABLE INPUTS / OUTPUTS	6 digital + 3 analogue senders / 6 outputs
KEY FEATURES	Auto-start, AMF control, LED indicators and event logging

MODEL P20-BWP	21.2 kVA ESP	17.0 kW ESP	19.6 kVA PRP	15.7 kW PRP
50 HZ PRIME & STANDBY POWER				



DIMENSIONS & WEIGHT			
LENGTH (mm) 2240	WIDTH (mm) 1038	HEIGHT (mm) 1378	WEIGHT (kg) 880.75

Configuration: UK/EU Canopied / frame 1900E / tank 80 L

RATING CONDITIONS	
RATING BASIS	NTP conditions; confirm project derating requirements
FREQUENCY / SPEED	50 Hz / 1500 RPM
VOLTAGE / CONNECTION	400/230 V / series star
POWER FACTOR	0.8 lagging
COOLING PACKAGE	Tropical radiator rated for 50 C ambient
STANDARDS	ISO 8528; IEC 60034

DISCLAIMER

Ratings and component data are transcribed from the corresponding Welland Power configuration for 400 V, three-phase, 50 Hz operation and checked against the listed Perkins engine and Stamford alternator models. Dimensions, weight, tank and noise data apply only to the configuration stated above. Images are illustrative and are intentionally common across this range. Final build specification, GA drawing, breaker selection and site derating must be confirmed at order. Manufacturer specifications may change without notice.

Dealer contact details: