

MODEL P283-BWP

308 kVA
ESP

246 kW
ESP

283 kVA
PRP

226 kW
PRP

50 HZ | PRIME & STANDBY POWER



DIESEL ENGINE

ENGINE BRAND	Perkins
ENGINE MODEL	1506A-E88TAG4
ASPIRATION	Turbocharged
GOVERNOR	Electronic

ALTERNATOR

BRAND	Stamford
MODEL	S4L1D-D41
EXCITATION	Self Excited
INSULATION CLASS	H
VOLTAGE REGULATION	1%
SPACE HEATER	Optional

GENERATOR SET - KEY PARAMETERS

GENSET MODEL	P283-BWP
POWER PRP	283 kVA / 226 kW
POWER ESP	308 kVA / 246 kW
FREQUENCY / SPEED	50 Hz / 1500 RPM
OUTPUT VOLTAGE	400 / 230 V
WIRING METHOD	3-phase, 4-wire
POWER FACTOR	0.8 pf lagging
ENCLOSURE / NOISE	Canopied; 76 dB(A) @ 7 m

AUXILIARY SYSTEMS

CONTROL MODULE	Deep Sea DSE 7320 MKII
COOLING RADIATOR	Tropical, 50 C ambient
FULL-LOAD CURRENT	444.6 A at ESP
CIRCUIT BREAKER	Optional; sized to generator rating
COOLANT HEATER	Optional
STARTING BATTERY	Wet battery, maintenance-free
FUEL TANK	500 litres
BASE FRAME	Base tank + AVM + battery holder



Acoustic Vents



Premium DSE Controller



Easy Maintenance

STANDARD SUPPLY

INSTALLATION ACCESSORIES	AVMs, exhaust connection, silencer, standard connection parts and tool kit.
--------------------------	---

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

MODEL P283-BWP

308 kVA

ESP

246 kW

ESP

283 kVA

PRP

226 kW

PRP

50 HZ | PRIME & STANDBY POWER

ENGINE TECHNICAL PARAMETERS - PERKINS 1506A-E88TAG4 - DIESEL

STRUCTURAL FORM	4 Stroke	COMBUSTION SYSTEM	Direct Injection
NUMBER OF CYLINDERS	6 (In Line)	OIL CAPACITY	41.0L
DISPLACEMENT	8.8L	COOLANT CAPACITY	33.2L
BORE / STROKE	112mm / 149mm	MAX EXHAUST TEMP.	576°C
COMPRESSION RATIO	16.1:1	EU EMISSIONS	None
ASPIRATION	Turbocharged		
GOVERNOR	Electronic		
COOLING METHOD	Liquid Cooled		
SPEED	1500 RPM		

FUEL CONSUMPTION

50% Load 31.60 litres/hour	75% Load 45.80 litres/hour	100% Load 60.20 litres/hour	110% Load 66.30 litres/hour
-------------------------------	-------------------------------	--------------------------------	--------------------------------

ALTERNATOR TECHNICAL PARAMETERS - STAMFORD S4L1D-D41

RATED POWER AT 400 V	ESP 340.0 kVA / PRP 310.0 kVA
NUMBER OF POLES / LEADS	4 / 12
WINDING NUMBER	311
BEARING TYPE	1 bearing
PROTECTION CLASS	IP23
INSULATION CLASS	H
EXCITATION METHOD	Self Excited
VOLTAGE REGULATION	AS440 AVR / 1%
HARMONIC CONTENT	<5.00%
SHORT-CIRCUIT CAPACITY	>300%
SPACE HEATER	Optional

CONTROL SYSTEM - DSE 7320 MKII

BRAND	Deep Sea Electronics
MODEL	DSE 7320 MKII
CONFIGURABLE INPUTS / OUTPUTS	6 digital + 3 analogue senders / 6 outputs
KEY FEATURES	Auto-start, AMF control, LED indicators and event logging

MODEL P283-BWP

308 kVA
ESP

246 kW
ESP

283 kVA
PRP

226 kW
PRP

50 HZ | PRIME & STANDBY POWER



DIMENSIONS & WEIGHT			
LENGTH (mm) 3958	WIDTH (mm) 1504	HEIGHT (mm) 2384	WEIGHT (kg) 3500.65

Configuration: UK/EU Canopied / frame 2900E / tank 500 L

RATING CONDITIONS	
RATING BASIS	NTP conditions; confirm project derating requirements
FREQUENCY / SPEED	50 Hz / 1500 RPM
VOLTAGE / CONNECTION	400/230 V / series star
POWER FACTOR	0.8 lagging
COOLING PACKAGE	Tropical radiator rated for 50 C ambient
STANDARDS	ISO 8528; IEC 60034

DISCLAIMER

Ratings and component data are transcribed from the corresponding Welland Power configuration for 400 V, three-phase, 50 Hz operation and checked against the listed Perkins engine and Stamford alternator models. Dimensions, weight, tank and noise data apply only to the configuration stated above. Images are illustrative and are intentionally common across this range. Final build specification, GA drawing, breaker selection and site derating must be confirmed at order. Manufacturer specifications may change without notice.

Dealer contact details: