

MODEL P310-BWP


340 kVA
ESP

272 kW
ESP

310 kVA
PRP

248 kW
PRP

50 HZ | PRIME & STANDBY POWER



DIESEL ENGINE	
ENGINE BRAND	Perkins
ENGINE MODEL	2206A-E13TAG2
ASPIRATION	Turbocharged
GOVERNOR	Electronic

ALTERNATOR	
BRAND	Stamford
MODEL	S4L1D-D41
EXCITATION	Self Excited
INSULATION CLASS	H
VOLTAGE REGULATION	1%
SPACE HEATER	Optional

GENERATOR SET - KEY PARAMETERS	
GENSET MODEL	P310-BWP
POWER PRP	310 kVA / 248 kW
POWER ESP	340 kVA / 272 kW
FREQUENCY / SPEED	50 Hz / 1500 RPM
OUTPUT VOLTAGE	400 / 230 V
WIRING METHOD	3-phase, 4-wire
POWER FACTOR	0.8 pf lagging
ENCLOSURE / NOISE	Canopied; 76 dB(A) @ 7 m

AUXILIARY SYSTEMS	
CONTROL MODULE	Deep Sea DSE 7320 MKII
COOLING RADIATOR	Tropical, 50 C ambient
FULL-LOAD CURRENT	490.7 A at ESP
CIRCUIT BREAKER	Optional; sized to generator rating
COOLANT HEATER	Optional
STARTING BATTERY	Wet battery, maintenance-free
FUEL TANK	500 litres
BASE FRAME	Base tank + AVM + battery holder



Acoustic Vents



Premium DSE Controller



Easy Maintenance

STANDARD SUPPLY	
INSTALLATION ACCESSORIES	AVMs, exhaust connection, silencer, standard connection parts and tool kit.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

MODEL P310-BWP

340 kVA

ESP

272 kW

ESP

310 kVA

PRP

248 kW

PRP

50 HZ | PRIME & STANDBY POWER

ENGINE TECHNICAL PARAMETERS - PERKINS 2206A-E13TAG2 - DIESEL

STRUCTURAL FORM	4 Stroke	COMBUSTION SYSTEM	Direct Injection
NUMBER OF CYLINDERS	6 (In Line)	OIL CAPACITY	40.0L
DISPLACEMENT	12.5L	COOLANT CAPACITY	51.4L
BORE / STROKE	130mm / 157mm	MAX EXHAUST TEMP.	630 °C
COMPRESSION RATIO	16.3:1	EU EMISSIONS	None
ASPIRATION	Turbocharged		
GOVERNOR	Electronic		
COOLING METHOD	Liquid Cooled		
SPEED	1500 RPM		

FUEL CONSUMPTION

50% Load 37.00 litres/hour	75% Load 54.00 litres/hour	100% Load 71.00 litres/hour	110% Load 80.00 litres/hour
-------------------------------	-------------------------------	--------------------------------	--------------------------------

ALTERNATOR TECHNICAL PARAMETERS - STAMFORD S4L1D-D41

RATED POWER AT 400 V	ESP 340.0 kVA / PRP 310.0 kVA
NUMBER OF POLES / LEADS	4 / 12
WINDING NUMBER	311
BEARING TYPE	1 bearing
PROTECTION CLASS	IP23
INSULATION CLASS	H
EXCITATION METHOD	Self Excited
VOLTAGE REGULATION	AS440 AVR / 1%
HARMONIC CONTENT	<5.00%
SHORT-CIRCUIT CAPACITY	>300%
SPACE HEATER	Optional

CONTROL SYSTEM - DSE 7320 MKII

BRAND	Deep Sea Electronics
MODEL	DSE 7320 MKII
CONFIGURABLE INPUTS / OUTPUTS	6 digital + 3 analogue senders / 6 outputs
KEY FEATURES	Auto-start, AMF control, LED indicators and event logging

MODEL P310-BWP

340 kVA

ESP

272 kW

ESP


310 kVA

PRP

248 kW

PRP

50 HZ | PRIME & STANDBY POWER



DIMENSIONS & WEIGHT

LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	WEIGHT (kg)
3958	1504	2384	3846.1

Configuration: UK/EU Canopied / frame 2900E / tank 500 L

RATING CONDITIONS

RATING BASIS	NTP conditions; confirm project derating requirements
FREQUENCY / SPEED	50 Hz / 1500 RPM
VOLTAGE / CONNECTION	400/230 V / series star
POWER FACTOR	0.8 lagging
COOLING PACKAGE	Tropical radiator rated for 50 C ambient
STANDARDS	ISO 8528; IEC 60034

DISCLAIMER

Ratings and component data are transcribed from the corresponding Welland Power configuration for 400 V, three-phase, 50 Hz operation and checked against the listed Perkins engine and Stamford alternator models. Dimensions, weight, tank and noise data apply only to the configuration stated above. Images are illustrative and are intentionally common across this range. Final build specification, GA drawing, breaker selection and site derating must be confirmed at order. Manufacturer specifications may change without notice.

Dealer contact details: