

MODEL P702-BWP


774 kVA  
ESP

619 kW  
ESP

702 kVA  
PRP

562 kW  
PRP

50 HZ | PRIME & STANDBY POWER



| DIESEL ENGINE |               |
|---------------|---------------|
| ENGINE BRAND  | Perkins       |
| ENGINE MODEL  | 2806A-E18TAG4 |
| ASPIRATION    | Turbocharged  |
| GOVERNOR      | Electronic    |

| ALTERNATOR         |           |
|--------------------|-----------|
| BRAND              | Stamford  |
| MODEL              | S6L1D-C41 |
| EXCITATION         | PMG       |
| INSULATION CLASS   | H         |
| VOLTAGE REGULATION | 0.5%      |
| SPACE HEATER       | Optional  |

| GENERATOR SET - KEY PARAMETERS |                          |
|--------------------------------|--------------------------|
| GENSET MODEL                   | P702-BWP                 |
| POWER PRP                      | 702 kVA / 562 kW         |
| POWER ESP                      | 774 kVA / 619 kW         |
| FREQUENCY / SPEED              | 50 Hz / 1500 RPM         |
| OUTPUT VOLTAGE                 | 400 / 230 V              |
| WIRING METHOD                  | 3-phase, 4-wire          |
| POWER FACTOR                   | 0.8 pf lagging           |
| ENCLOSURE / NOISE              | Canopied; 76 dB(A) @ 7 m |

| AUXILIARY SYSTEMS |                                     |
|-------------------|-------------------------------------|
| CONTROL MODULE    | Deep Sea DSE 7320 MKII              |
| COOLING RADIATOR  | Tropical, 50 C ambient              |
| FULL-LOAD CURRENT | 1117.2 A at ESP                     |
| CIRCUIT BREAKER   | Optional; sized to generator rating |
| COOLANT HEATER    | Optional                            |
| STARTING BATTERY  | Wet battery, maintenance-free       |
| FUEL TANK         | 1120 litres                         |
| BASE FRAME        | Base tank + AVM + battery holder    |



Acoustic Vents



Premium DSE Controller



Easy Maintenance

| STANDARD SUPPLY          |                                                                             |
|--------------------------|-----------------------------------------------------------------------------|
| INSTALLATION ACCESSORIES | AVMs, exhaust connection, silencer, standard connection parts and tool kit. |

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

MODEL P702-BWP

774 kVA

ESP

619 kW

ESP

702 kVA

PRP

562 kW

PRP

50 HZ | PRIME & STANDBY POWER

ENGINE TECHNICAL PARAMETERS - PERKINS 2806A-E18TAG4 - DIESEL

|                     |               |                   |                  |
|---------------------|---------------|-------------------|------------------|
| STRUCTURAL FORM     | 4 Stroke      | COMBUSTION SYSTEM | Direct Injection |
| NUMBER OF CYLINDERS | 6 (In Line)   | OIL CAPACITY      | 68.0L            |
| DISPLACEMENT        | 18.1L         | COOLANT CAPACITY  | 110.0L           |
| BORE / STROKE       | 145mm / 183mm | MAX EXHAUST TEMP. | 465 °C           |
| COMPRESSION RATIO   | 14:1          | EU EMISSIONS      | None             |
| ASPIRATION          | Turbocharged  |                   |                  |
| GOVERNOR            | Electronic    |                   |                  |
| COOLING METHOD      | Liquid Cooled |                   |                  |
| SPEED               | 1500 RPM      |                   |                  |

FUEL CONSUMPTION

|                               |                                |                                 |                                 |
|-------------------------------|--------------------------------|---------------------------------|---------------------------------|
| 50% Load<br>76.00 litres/hour | 75% Load<br>108.00 litres/hour | 100% Load<br>145.00 litres/hour | 110% Load<br>160.00 litres/hour |
|-------------------------------|--------------------------------|---------------------------------|---------------------------------|

ALTERNATOR TECHNICAL PARAMETERS - STAMFORD S6L1D-C41

|                         |                               |
|-------------------------|-------------------------------|
| RATED POWER AT 400 V    | ESP 860.0 kVA / PRP 810.0 kVA |
| NUMBER OF POLES / LEADS | 4 / 6                         |
| WINDING NUMBER          | 312                           |
| BEARING TYPE            | 1 bearing                     |
| PROTECTION CLASS        | IP23                          |
| INSULATION CLASS        | H                             |
| EXCITATION METHOD       | PMG                           |
| VOLTAGE REGULATION      | MX321 AVR / 0.5%              |
| HARMONIC CONTENT        | <5.00%                        |
| SHORT-CIRCUIT CAPACITY  | >300%                         |
| SPACE HEATER            | Optional                      |

CONTROL SYSTEM - DSE 7320 MKII

|                               |                                                           |
|-------------------------------|-----------------------------------------------------------|
| BRAND                         | Deep Sea Electronics                                      |
| MODEL                         | DSE 7320 MKII                                             |
| CONFIGURABLE INPUTS / OUTPUTS | 6 digital + 3 analogue senders / 6 outputs                |
| KEY FEATURES                  | Auto-start, AMF control, LED indicators and event logging |

MODEL P702-BWP

774 kVA  
ESP

619 kW  
ESP

702 kVA  
PRP

562 kW  
PRP

50 HZ | PRIME & STANDBY POWER



| DIMENSIONS & WEIGHT |                    |                     |                        |
|---------------------|--------------------|---------------------|------------------------|
| LENGTH (mm)<br>4908 | WIDTH (mm)<br>2164 | HEIGHT (mm)<br>2658 | WEIGHT (kg)<br>7092.85 |

Configuration: UK/EU Canopied / frame 5100E / tank 1120 L

| RATING CONDITIONS    |                                                       |
|----------------------|-------------------------------------------------------|
| RATING BASIS         | NTP conditions; confirm project derating requirements |
| FREQUENCY / SPEED    | 50 Hz / 1500 RPM                                      |
| VOLTAGE / CONNECTION | 400/230 V / series star                               |
| POWER FACTOR         | 0.8 lagging                                           |
| COOLING PACKAGE      | Tropical radiator rated for 50 C ambient              |
| STANDARDS            | ISO 8528; IEC 60034                                   |

DISCLAIMER

Ratings and component data are transcribed from the corresponding Welland Power configuration for 400 V, three-phase, 50 Hz operation and checked against the listed Perkins engine and Stamford alternator models. Dimensions, weight, tank and noise data apply only to the configuration stated above. Images are illustrative and are intentionally common across this range. Final build specification, GA drawing, breaker selection and site derating must be confirmed at order. Manufacturer specifications may change without notice.

Dealer contact details: