

MODEL P741-BWP


814 kVA
ESP

651 kW
ESP

741 kVA
PRP

593 kW
PRP

50 HZ | PRIME & STANDBY POWER



DIESEL ENGINE	
ENGINE BRAND	Perkins
ENGINE MODEL	4006-23TAG2A
ASPIRATION	Turbocharged
GOVERNOR	Electronic

ALTERNATOR	
BRAND	Stamford
MODEL	S6L1D-C41
EXCITATION	PMG
INSULATION CLASS	H
VOLTAGE REGULATION	0.5%
SPACE HEATER	Optional

GENERATOR SET - KEY PARAMETERS	
GENSET MODEL	P741-BWP
POWER PRP	741 kVA / 593 kW
POWER ESP	814 kVA / 651 kW
FREQUENCY / SPEED	50 Hz / 1500 RPM
OUTPUT VOLTAGE	400 / 230 V
WIRING METHOD	3-phase, 4-wire
POWER FACTOR	0.8 pf lagging
ENCLOSURE / NOISE	Open; Not published - confirm by configuration

AUXILIARY SYSTEMS	
CONTROL MODULE	Deep Sea DSE 7320 MKII
COOLING RADIATOR	Tropical, 50 C ambient
FULL-LOAD CURRENT	1174.9 A at ESP
CIRCUIT BREAKER	Optional; sized to generator rating
COOLANT HEATER	Optional
STARTING BATTERY	Wet battery, maintenance-free
FUEL TANK	0 litres
BASE FRAME	Base tank + AVM + battery holder



Acoustic Vents



Premium DSE Controller



Easy Maintenance

STANDARD SUPPLY	
INSTALLATION ACCESSORIES	AVMs, exhaust connection, silencer, standard connection parts and tool kit.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

MODEL P741-BWP

814 kVA

ESP

651 kW

ESP

741 kVA

PRP

593 kW

PRP

50 HZ | PRIME & STANDBY POWER

ENGINE TECHNICAL PARAMETERS - PERKINS 4006-23TAG2A - DIESEL

STRUCTURAL FORM	4 Stroke	COMBUSTION SYSTEM	Direct Injection
NUMBER OF CYLINDERS	6 (In Line)	OIL CAPACITY	113L
DISPLACEMENT	22.92L	COOLANT CAPACITY	120L
BORE / STROKE	160mm / 195mm	MAX EXHAUST TEMP.	430 °C
COMPRESSION RATIO	13.6:1	EU EMISSIONS	None
ASPIRATION	Turbocharged		
GOVERNOR	Electronic		
COOLING METHOD	Liquid Cooled		
SPEED	1500 RPM		

FUEL CONSUMPTION

50% Load 80.00 litres/hour	75% Load 117.00 litres/hour	100% Load 155.00 litres/hour	110% Load 169.00 litres/hour
-------------------------------	--------------------------------	---------------------------------	---------------------------------

ALTERNATOR TECHNICAL PARAMETERS - STAMFORD S6L1D-C41

RATED POWER AT 400 V	ESP 860.0 kVA / PRP 810.0 kVA
NUMBER OF POLES / LEADS	4 / 6
WINDING NUMBER	312
BEARING TYPE	1 bearing
PROTECTION CLASS	IP23
INSULATION CLASS	H
EXCITATION METHOD	PMG
VOLTAGE REGULATION	MX321 AVR / 0.5%
HARMONIC CONTENT	<5.00%
SHORT-CIRCUIT CAPACITY	>300%
SPACE HEATER	Optional

CONTROL SYSTEM - DSE 7320 MKII

BRAND	Deep Sea Electronics
MODEL	DSE 7320 MKII
CONFIGURABLE INPUTS / OUTPUTS	6 digital + 3 analogue senders / 6 outputs
KEY FEATURES	Auto-start, AMF control, LED indicators and event logging

MODEL P741-BWP

814 kVA
ESP

651 kW
ESP

741 kVA
PRP

593 kW
PRP

50 HZ | PRIME & STANDBY POWER



DIMENSIONS & WEIGHT			
LENGTH (mm) 4000	WIDTH (mm) 1690	HEIGHT (mm) 2425	WEIGHT (kg) 5253.15

Configuration: Export Open / frame GenericPerkins4000 / tank 0 L

RATING CONDITIONS	
RATING BASIS	NTP conditions; confirm project derating requirements
FREQUENCY / SPEED	50 Hz / 1500 RPM
VOLTAGE / CONNECTION	400/230 V / series star
POWER FACTOR	0.8 lagging
COOLING PACKAGE	Tropical radiator rated for 50 C ambient
STANDARDS	ISO 8528; IEC 60034

DISCLAIMER

Ratings and component data are transcribed from the corresponding Welland Power configuration for 400 V, three-phase, 50 Hz operation and checked against the listed Perkins engine and Stamford alternator models. Dimensions, weight, tank and noise data apply only to the configuration stated above. Images are illustrative and are intentionally common across this range. Final build specification, GA drawing, breaker selection and site derating must be confirmed at order. Manufacturer specifications may change without notice.

Dealer contact details: